




# SPLIT MURO



ECO-09INT/EXT    ECO-12INT/EXT    ECO-18INT/EXT    ECO-24INT/EXT

Voltaje / Frecuencia	V-Hz	220-240V-50 Hz	220-240V-50 Hz	220-240V-50 Hz	220-240V-50 Hz
Capacidad (Frió/Calor)	BTU	9000 / 9700	12000 / 13000	18000 / 18100	24000 / 25000
Consumo (Frió/Calor)	W	870 / 760	1120 / 1020	2200 / 1880	2200 / 2500
Corriente (Frió/Calor)	A	4 / 3,5	5,1 / 4,7	7,4 / 7,9	9,5 / 9,5
Dimensiones Int.(Al/An/Pr.)	Unidad mm	800/290/196	800/290/196	860/292/205	1080/330/220
Dimensiones Ext.(Al/An/Pr.)	Unidad mm	600/480/250	700/540/255	770/520/280	845/680/310
Peso (Unidad Int./Unidad Ext.)	Kg	10 / 26	10 / 30	11 / 41	15 / 51
Función Reinicio Automático		SI	SI	SI	SI
Refrigerante		Ecológico R410A	Ecológico R410A	Ecológico R410A	Ecológico R410A
Área cobertura	Mt2	12-16	16-22	22-34	35-45
Eficiencia Energética		A	A	A	C
Certificado N°		E013-03-8353	E013-03-8354	E013-03-8978	E013-03-8355